



517.32564

SURFACE MOUNTING SOCKET

32A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz
60Hz Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|----------------------------|---|---|
| Type of product | SURFACE MOUNTING SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | OPTIMA Series | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | SURFACE MOUNTING SOCKET | | |
| Mounting version | SURFACE MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 32A | | |
| Poles | 3P+E | | |
| Hour position | 3h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 380V 50Hz / 440V 60Hz | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67/IP69 | | |
| Protection degree IK | IK08 | | |
| Types of available outlets | ANGLED | | |
| Terminals | Screw terminals | | |

| | |
|------------------|--------------|
| Contact material | CuZn (brass) |
| Cable entry | M32X1,5 |