

HDC-CR10-3S GR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The sturdy CR10 module frames are available in polycarbonate or die-cast zinc.

The frames are designed so that 3 individual modules or corresponding double modules can be installed. The CR10 frames are designed to fit the size-4 housings.

General ordering data

Version	Heavy-duty connectors, HDC insert, ConCept frame
Order No.	1758460000
Type	HDC-CR10-3S GR
GTIN (EAN)	4032248019687
Qty.	5 Stück

Erstellungs-Datum February 20, 2021 10:29:13 AM CET

Katalogstand 12.02.2021 / Technische Änderungen vorbehalten

HDC-CR10-3S GR

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technische Daten

Dimensions and weights

Depth	64 mm	Depth (inches)	2.52 inch
Height	35 mm	Height (inches)	1.378 inch
Net weight	37.14 g	Width	34 mm
Width (inches)	1.339 inch		

Temperatures

Limit temperature -40 °C ... 125 °C

ConCept Pneumatic module

Colour	beige	UL 94 flammability rating	V-0
--------	-------	---------------------------	-----

Dimensions

Height of plug	35 mm	Total length base	64 mm
Width	34 mm		

General data

Material	Polycarbonate	Number of poles	1
Series	ConCept frame	Size	4
Type	Pin	UL 94 flammability rating	V-0

Connection data PE

Connection type PE	Screw connection	Tightening torque, max. PE connection	1.5 Nm
Tightening torque, min. PE connection	1.2 Nm		

Version

Material	Polycarbonate	Size	4
Wire connection cross section AWG, max.	AWG 14		

Classifications

ETIM 6.0	EC002312	ETIM 7.0	EC002312
ECLASS 9.0	27-44-02-06	ECLASS 9.1	27-44-02-06
ECLASS 10.0	27-44-02-06	ECLASS 11.0	27-44-02-06

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	FL FIELDWIRING EN
Engineering Data	STEP
Engineering Data	WSCAD

Erstellungs-Datum February 20, 2021 10:29:13 AM CET

Katalogstand 12.02.2021 / Technische Änderungen vorbehalten