

TECHNICAL INFORMATIONS


GLOBE

10W 4500K BRANCO

Plafond de Jardim de luz direta com corpo em alumínio e difusor em policarbonato. Uma solução simples e elegante para qualquer espaço exterior.

Direct garden light ceiling with aluminum body and polycarbonate diffuser. A simple and elegant solution for any outdoor space.

Plafón de luz directa para jardín con cuerpo de aluminio y difusor de policarbonato. Una solución simple y elegante para cualquier espacio exterior.



ILAR-00952

REFERENCE

Reference	ILAR-00952
LED Brand	SMD Led
Body Material	Aluminium + PC Diffuser
Housing Colour	White
Nominal Lifetime (EOL end of life)	30000H
Surface / Recessed	Surface
Dimmable	NO
Installation	Surface

DIMENSION & WEIGHT

Lenght	Ø200mm
Width	Ø200mm
Height	55mm
Packaging Unit	Carton Box 10 pcs
Gross Weight	-
Volume	-

PHOTOMETRICAL DATA

Total Luminous Flux	1000lm
Luminous Efficacy	100lm/W
Beam Angle	120°
Colour Temperature	4500K
Colour Rendering Index	>80

ELECTRICAL AND OPERATING DATA

Nominal Wattage	10W
Nominal Voltage	220-240V
Operating Frequency	50/60Hz
Operating Temperature	- 20° C to + 50° C
Starting Time 100% ON	0.000s
ON/OFF Cycles	>20000


ENERGY LABEL & STANDARS

Energy Label	A+
Energy Consumption KWH/1000H	-
Type of Protection	IP54
Protection Class	Class II
Protection Class IK (shock resistance)	IK6


CERTIFICATIONS

2014/30/EU (EMC Directive)	YES
2014/35/EU (LVD Directive)	YES
ROHS	YES
ENEC	NO
Warranty	3 YEARS

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

