

Product datasheet

Specifications



switch-disconnector iSW-NA - 1P + N - 63 A

A9S70663

! Discontinued on: 01 November 2020

! End-of-service on: 03 November 2020

! Discontinued

A9S70663 has not been replaced. Please contact your customer care centre for more information.

Main

Range	Acti 9
Product name	Acti9 iSW-NA
Product or component type	Switch disconnecter
Device short name	ISW-NA
Device application	Control Isolation
Poles description	1P + N
Neutral position	Left
Utilisation category	AC-22A conforming to EN/IEC 60947-3
Suitability for isolation	Yes conforming to EN/IEC 60947-3

Complementary

[Ie] rated operational current	63 A at 230/240 V AC 50/60 Hz
[Ue] rated operational voltage	230/240 V AC 50/60 Hz
[Icm] rated short-circuit making capacity	5 kA switch-disconnector alone
[Icw] rated short-time withstand current	1.26 kA during 1 s
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60947-3
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-3
Control type	Remote tripping Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top or bottom: YES
9 mm pitches	4
Height	85 mm

Width	36 mm
Depth	74 mm
Net weight	0.17 kg
Colour	White
Mechanical durability	20000 cycles
Electrical durability	15000 cycles
Connections - terminals	Tunnel type terminals (top or bottom) 1 cable(s) 1...25 mm ² flexible with cable end Tunnel type terminals (top or bottom) 1 cable(s) 1...25 mm ² flexible without cable end Tunnel type terminals (top or bottom) 1 cable(s) 1...35 mm ² rigid without cable end
Wire stripping length	14 mm
Tightening torque	3.5 N.m
Product compatibility	Tripping release

Environment

Standards	EN 60947-3 IEC 60947-3
IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-3
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	185 g
Package 1 Height	4 cm
Package 1 width	8 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	54
Package 2 Weight	10.477 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Package 3 Height	30 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 months
