



Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product name | TeSys LE |
| Device short name | LE1D |
| Product or component type | Enclosed DOL starter |
| Device application | Standard |
| Utilisation category | AC-3 |
| Device composition | Thermal overload relay ordered separately Contactor |
| Control type | Push-button start green I Push-button stop/reset red O |

Complementary

| | |
|--|---|
| [Ie] rated operational current | 25 A AC-3 |
| Motor power kW | 11 KW at 380/400 V AC 50/60 Hz 11 KW at 415 V AC 50/60 Hz 11 KW at 440 V AC 50/60 Hz 15 KW at 500 V AC 50/60 Hz 15 KW at 660/690 V AC 50/60 Hz 5.5 KW at 220/230 V AC 50/60 Hz |
| [Ithe] conventional enclosed thermal current | 25 A |
| [Uc] control circuit voltage | 400 V AC 50/60 Hz |
| Cable entry number | 2 ISO20 top 2 ISO20 bottom 2 Pg 16 bottom 2 ISO25 top 2 Pg 21 bottom 2 ISO25 bottom |
| Width | 101 Mm |
| Height | 201 Mm |
| Depth | 153.5 Mm |
| Net weight | 1.015 Kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Material | Polycarbonate |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.243 Kg |
| Package 1 Height | 16.3 Cm |
| Package 1 width | 20 Cm |
| Package 1 Length | 25 Cm |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 22 |
| Package 2 Weight | 40.35 Kg |
| Package 2 Height | 75 Cm |
| Package 2 width | 80 Cm |
| Package 2 Length | 60 Cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**