



## Main

Range of product	Harmony XAC
Product or component type	Head for push-button
Component name	XACA

## Complementary

Marking	Unmarked
Operator additional information	Booted
Cap/operator or lens colour	White
Product compatibility	XACA..
Mounting location	Front of enclosure
Sale per indivisible quantity	10
Standards	CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60204-32 UL 508
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 50102
Net weight	0.01 Kg

## Packing Units

Package 1 Weight	0.009 Kg
Package 1 Height	0.300 Dm
Package 1 width	1.100 Dm
Package 1 Length	1.000 Dm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

RoHS exemption information [Yes](#)

---

China RoHS Regulation [China RoHS Declaration](#)

---

**Contractual warranty**

---

Warranty 18 months

---

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------